Index to

EXPERIMENTAL MECHANICS

Volume 40, 2000

TITLE INDEX

Analysis of Deadweight Oscillation in a Deadweight Force Machine Using a Build-up System—D.-I. Kang and B.-D. Lim, 83-89 (Mar.).

Best Achievable Modal Eigenvectors in Structural Damage Detection—S. Ricci, 425 (Dec.).

Blind-hole Residual Stress Determination Using Optical Interferometry—S. T. Lin, 60-68 (Mar.).

A Combination Optical Method of Lateral Shearing Interferometry and Caustics—S. Prabhu and J. Lambros, 376 (Dec.).

Comments on "Interpretation of Experimental Data for Poisson's Ratio of Highly Nonlinear Materials"—P.A.A. Laura, C. A. Rossit and J. C. Paloto, 430 (Dec.).

Confined Compression: A Stable Homogeneous Deformation for Constitutive Characterization—Z. Ma and K. Ravi-Chandar, 38-45 (Mar.).

Damage Process Detection of a Ceramic Tile System by Acoustic Emission—W. Yao, Z. Li and M. Qi, 265-270 (Sept.).

Deep Punching PMMA—S. Satapathy and S. Bless, 31-37 (Mar.).

Deformation Measurements by Digital Image Correlation: Implementation of a Second-order Displacement Gradient—H. Lu and P. D. Cary, 393 (Dec.).

Determination of the Plastic Work Converted to Heat Using Radiometry—D. Macdougall, 298-306 (Sept.).

Development of an Electromechanical Triaxial Test Facility for Composite Materials—J. S. Welsh and D. F. Adams, 312-320 (Sept.).

A Device to Regulate Rotational Speed Using a Rotating Regulator with Electrorheological Fluid—K. Shimada and T. Fujita, 231-240 (June).

Discussion of "Novel Procedure for Complete In-plane Composite Characterization Using a Single T-shaped Specimen"—R. Prabhakaran, 96-97 (Mar.).

Dynamic Compression-shear Response of Brittle Materials with Specimen Recovery—H. D. Espinosa, A. Patanella and Y. Xu, 321-330(Sept.).

Effects of Joining Techniques on Impact Perforation Resistance of Assembled Composite Plates—D. Liu and B. B. Raju, 46-53 (Mar.).

Expansion of Cylindrical Shells Subjected to Internal Explosive Detonations—R. L. Martineau, C. A. Anderson and F. W. Smith, 219-225 (June).

Experimental Analysis of Rolling Contact Stresses in a Viscoelastic Strip—S. Yoneyama, J. Gotoh and M. Takashi, 203-210 (June).

Experimental Evidence of Macroscopic Plastic Flow Nonhomogeneity Development in Uniaxial Tensile Test Samples—F. Zeides and I. Roman, 261-264 (Sept.).

Experimental Evidence of Pochammer-Chree Strain Variations in Elastic Cylinders—A. Tyas and A. J. Watson, 331-337 (Sept.).

An Experimental Method for Determining Dynamic Fracture Toughness—C. H. Popelar, C. E. Anderson, Jr. and A. Nagy, 401 (Dec.).

Fracture Toughness of Fabrics as Composite Reinforcements—D. L. Davidson, D. P. Nicolella and B. S. Spigel, 408 (Dec.).

French Round-robin Test of X-ray Stress Determination on a Shot-peened Steel—M. François, F. Convert and S. Branchu, 361 (Dec.).

High-magnification Moiré Interferometer for Crack Tip Analysis of Steels—F. A. La Porta, J. M. Huntley, T. E. Chung and R. G. Faulkner, 90-95 (Mar.).

Identification of Stiffness Properties of Composite Tubes from Dynamic Tests—J. Cunha and J. Piranda, 211-218 (June).

Infrared Temperature Sensing of Mechanically Loaded Specimens: Thermal Analysis—Y. Rabin and D. Rittel, 197-202 (June).

Initiation and Growth of Wrinkling Due to Nonuniform Tension in Sheet Metal Forming—M. Li, R. L. Brazill and E. W. Chu, 180-189 (June).

An Intelligent Hybrid Method to Automatically Detect and Eliminate Experimental Measurement Errors for Linear Elastic Deformation Fields—T. Nishioka, K. Kurio and H. Nakabayashi, 170-179 (June).

Inversion of Speckle Interferometer Fringes for Hole-drilling Residual Stress Determinations—D. R. Schmitt and R. W. Hunt, 129-137 (June).

Limitation of Fourier Transform Photoelasticity: Influence of Isoclinics—A. Ajovalasit and B. Zuccarello, 384 (Dec.).

Measurement and Modeling of Stress Concentration around a Circular Notch—B. P. Arjyal, D. G. Katerelos, C. Filiou and C. Galiotis, 248-225 (Sept.).

Measurement of Bending Stresses in Shells of Arbitrary Shape Using the Reflection Moiré Method—C. A. Sciammarella, B. Trentadue and F. M. Sciammarella, 282-288 (Sept.).

Measurement of Curved-surface Deformation in Cylindrical Coordinates—P. F. Luo and J. N. Chen, 345 (Dec.).

Measurement of Residual Stress Using Interferometric Moiré: A New Insight—R. C. Schwarz, L. M. Kutt and J. M. Papazian, 271-281 (Sept.).

Measuring the Quality of Guitar Tone—S. Šali and J. Kopac, 242-247 (Sept.).

A Moiré Microscope for Finite Deformation Micro-mechanical Studies—N.-S. Liou and V. Prakash, 351 (Dec.).

A New Method for Circular Grid Analysis in the Sheet Metal Forming Test—C.-C. Wang, J. Lee, L.-W. Chen and H.-Y. Lai, 190-196 (June).

Noncontacting Strain Measurements at High Temperatures by the Digital Laser Speckle Technique—M. Anwander, B. G. Zagar, B. Weiss and H. Weiss, 98-105 (Mar.).

Nondestructive Testing Using Temporal Phase Evaluation in Speckle Interferometry—C. Joenathan, B. Franze, P. Haible and H. J. Tiziani, 106-111 (Mar.).

Notch Strengthening in Titanium Aluminides Under Monotonic Loading—J. G. Milke, J. L. Beuth and N. E. Biery, 415 (Dec.).

A Novel Dynamic Friction Experiment Using a Modified Kolsky Bar Apparatus—H. D. Espinosa, A. Patanella and M. Fischer, 138-153 (June).

On the Holographic Interferometry Fringe Gradient Method for Complete Surface Deformation Measurements—W. Szyszkowski and S. Boire, 164-165 (June).

Partition of Plastic Work into Heat and Stored Energy in Metals—J. Hodowany, G. Ravichandran, A. J. Rosakis and P. Rosakis, 113-123 (June).

Photoelastic Analysis of the Singular Stress Field in a Bimaterial Wedge—S. A. Meguid and M. A. Tan, 68-74 (Mar.).

A Quartz-crystal-embedded Split Hopkinson Pressure Bar for Soft Materials—W. Chen, F. Lu and B. Zhou, 1-6 (Mar.).

A Radial Compression Test for Plastic Flow Studies—B. Lamparter, S. Talbert and S. Tavoularis, 7-9 (Mar.).

Residual Strain Measurement in Composites Using the Cure-referencing Method—P. Ifju, X. Niu, B. Kilday, S.-C. Liu and S. Ettinger, 22-30 (Mar.).

Residual Stress Prediction and Determination in 7010 Aluminum Alloy Forgings—D. A. Tanner and J. S. Robinson, 75-82 (Mar.).
Response to the Discussion of the Paper "Novel Procedure for Complete In-plane Composite Characterization Using a Single T-shaped Specimen"—M. Grédiac, F. Pierron and Y. Surrel, 97 (Mar.).
Shape Measuremcnt and Control of Deployable Membrane Structures—A. K. Maji and M. A. Starnes, 154-159 (June).
A Simple Method for the Digital Determination of a Photoelastic Fringe Order—T. Y. Chen, 256-260 (Sept.).
Single-test Determination of the Friction Coefficient and Stress-strain Curve for Application in Metal-forming Analyses—A. F. Marcon, E. Bittencourt and G. J. Creus, 124-128 (June).
Stress Analysis of Weldments by Holographic Moiré and the Finite Element Method—C. A. Sciammarella, B. Singh, B. Trentadue and F. M. Sciammarella, 15-21 (Mar.).
A Technique for Dynamic Proportional Multiaxial Compression on Soft Materials—W. Chen and F. Lu, 226-230 (June).
Theoretical, Experimental and Computational Mechanics of Fracture in Constrained Interlayers—K. K. Schrems, M. E. Kassner and T. C. Kennedy, 307-311 (Sept.).
Thermoelastic Stress Analysis Applied to Fully Reversed Bending Fatigue—L. W. Byrd and M. A. Haney, 10-14 (Mar.).
Three-dimensional Mode Shapes of a Tire Using Experimental Modal Analysis—L. H. Yam, D. H. Guan and A. Q. Zhang, 369 (Dec.).
Torsional Split Hopkinson Bar Tests at Strain Rates above 10^4 s^{-1}—A. Gilat and C.-S. Cheng, 54-59 (Mar.).
A Transversely Suspended Accelerometer—J. A. Gilbert, N. Li and R. R. Gauthier, 160-163 (June).
Use of the Hole-drilling Method for Measuring Residual Stresses in Highly Stressed Shot-peened Surfaces—J. P. Nobre, M. Kornmeier, A. M. Dias and B. Scholtes, 289-297 (Sept.).

AUTHOR INDEX

Adams, D. F.—Development of an Electromechanical Triaxial Test Facility for Composite Materials, 312-320 (Sept.).
Ajovalasit, A.—Limitation of Fourier Transform Photoelasticity: Influence of Isoclinics, 384 (Dec.).
Anderson, C. A.—Expansion of Cylindrical Shells Subjected to Internal Explosive Detonations, 219-225 (June).
Anderson, C. E., Jr.—An Experimental Method for Determining Dynamic Fracture Toughness, 401 (Dec.).
Anwander, M.—Noncontacting Strain Measurements at High Temperatures by the Digital Laser Speckle Technique, 98-105 (Mar.).
Arjyal, B. P.—Measurement and Modeling of Stress Concentration around a Circular Notch, 248-225 (Sept.).
Beuth, J.—Notch Strengthening in Titanium Aluminides Under Monotonic Loading, 415 (Dec.).
Biery, N. E.—Notch Strengthening in Titanium Aluminides Under Monotonic Loading, 415 (Dec.).
Bittencourt, E.—Single-test Determination of the Friction Coefficient and Stress-strain Curve for Application in Metal-forming Analyses, 124-128 (June).
Bless, S.—Deep Punching PMMA, 31-38 (Mar.).
Boire, S.—On the Holographic Interferometry Fringe Gradient Method for Complete Surface Deformation Measurements, 164-169 (June).
Branchu, S.—French Round-robin Test of X-ray Stress Determination on a Shot-peened Steel, 361 (Dec.).
Brazill, R. L.—Initiation and Growth of Wrinkling Due to Nonuniform Tension in Sheet Metal Forming, 180-189 (June).
Byrd, L. W.—Thermoelastic Stress Analysis Applied to Fully Reversed Bending Fatigue, 10-14 (Mar.).
Cary, P. D.—Deformation Measurements by Digital Image Correlation: Implementation of a Second-order Displacement Gradient, 393 (Dec.).
Chen, J. N.—Measurement of Curved-surface Deformation in Cylindrical Coordinates, 345 (Dec.).
Chen, L.-W.—A New Method for Circular Grid Analysis in the Sheet Metal Forming Test, 190-196 (June).
Chen, T. Y.—A Simple Method for the Digital Determination of a Photoelastic Fringe Order, 256-260 (Sept.).
Chen, W.—A Quartz-crystal-embedded Split Hopkinson Pressure Bar for Soft Materials, 1-6 (Mar.).
Chen, W.—A Technique for Dynamic Proportional Multiaxial Compression on Soft Materials, 226-230 (June).
Cheng, C.-S.—Torsional Split Hopkinson Bar Tests at Strain Rates above 10^4 s^{-1}, 54-59 (Mar.).
Chu, E. W.—Initiation and Growth of Wrinkling Due to Nonuniform Tension in Sheet Metal Forming, 180-189 (June).
Chung, T. E.—High-magnification Moiré Interferometer for Crack Tip Analysis of Steels, 90-95 (Mar.).
Convert, F.—French Round-robin Test of X-ray Stress Determination on a Shot-peened Steel, 361 (Dec.).
Creus, G. J.—Single-test Determination of the Friction Coefficient and Stress-strain Curve for Application in Metal-Forming Analyses, 124-128 (June).
Cunha, J.—Identification of Stiffness Properties of Composite Tubes from Dynamic Tests, 211-218 (June).
Davidson, D. L.—Fracture Toughness of Fabrics as Composite Reinforcements, 408 (Dec.).
Dias, A. M.—Use of the Hole-drilling Method for Measuring Residual Stresses in Highly Stressed Shot-peened Surfaces, 289-297 (Sept.).
Espinosa, H. D.—Dynamic Compression-shear Response of Brittle Materials with Specimen Recovery, 321-330 (Sept.).
Espinosa, H. D.—A Novel Dynamic Friction Experiment Using a Modified Kolsky Bar Apparatus, 138-153 (June).
Ettinger, S.—Residual Strain Measurement in Composites Using the Cure-referencing Method, 22-30 (Mar.).
Faulkner, R. G.—High-magnification Moiré Interferometer for Crack Tip Analysis of Steels, 90-95 (Mar.).
Filiou, C.—Measurement and Modeling of Stress Concentration around a Circular Notch, 248-255 (Sept.).
Fischer, M.—A Novel Dynamic Friction Experiment Using a Modified Kolsky Bar Apparatus, 138-153 (June).
François, M.—French Round-robin Test of X-ray Stress Determination on a Shot-peened Steel, 361 (Dec.).
Franze, B.—Nondestructive Testing Using Temporal Phase Evaluation in Speckle Interferometry, 106-111 (Mar.).
Fujita, T.—A Device to Regulate Rotational Speed Using a Rotating Regulator with Electrorheological Fluid, 231-240 (June).
Galiotis, C.—Measurement and Modeling of Stress Concentration around a Circular Notch, 248-255 (Sept.).
Gauthier, R. R.—A Transversely Suspended Accelerometer, 160-163 (June).
Gilat, A.—Torsional Split Hopkinson Bar Tests at Strain Rates above 10^4 s^{-1}, 54-59 (Mar.).
Gilbert, J. A.—A Transversely Suspended Accelerometer, 160-163 (June).
Gotoh, J.—Experimental Analysis of Rolling Contact Stresses in a Viscoelastic Strip, 203-210 (June).
Grédiac, M.—Response to the Discussion of the Paper "Novel Procedure for Complete In-plane Composite Characterization Using a Single T-shaped Specimen," 97 (Mar.).
Guan, D. H.—Three-dimensional Mode Shapes of a Tire Using Experimental Modal Analysis, 369 (Dec.).
Haible, P.—Nondestructive Testing Using Temporal Phase Evaluation in Speckle Interferometry, 106-111 (Mar.).
Haney, M. A.—Thermoelastic Stress Analysis Applied to Fully Reversed Bending Fatigue, 10-14 (Mar.).
Hodowany, J.—Partition of Plastic Work into Heat and Stored Energy in Metals, 113-123 (June).
Hunt, R. W.—Inversion of Speckle Interferometer Fringes for Hole-drilling Residual Stress Determinations, 129-137 (June).
Huntley, J. M.—High-magnification Moiré Interferometer for Crack Tip Analysis of Steels, 90-95 (Mar.).
Ifju, P.—Residual Strain Measurement in Composites Using the Cure-referencing Method, 22-30 (Mar.).
Joenathan, C.—Nondestructive Testing Using Temporal Phase Evaluation in Speckle Interferometry, 106-111 (Mar.).
Kang, D.-I.—Analysis of Deadweight Oscillation in a Deadweight Force Machine Using a Build-up System, 83-89 (Mar.).
Kassner, M. E.—Theoretical, Experimental and Computational Mechanics of Fracture in Constrained Interlayers, 307-311 (Sept.).

Katerelos, D. G.—Measurement and Modeling of Stress Concentration around a Circular Notch, 248-255 (Sept.).
Kennedy, T. C.—Theoretical, Experimental and Computational Mechanics of Fracture in Constrained Interlayers, 307-311(Sept.).
Kilday, B.—Residual Strain Measurement in Composites Using the Cure-referencing Method, 22-30 (Mar.).
Kopac, J.—Measuring the Quality of Guitar Tone, 242-247 (Sept.).
Kommeier, M.—Use of the Hole-drilling Method for Measuring Residual Stresses in Highly Stressed Shot-peened Surfaces, 289-297 (Sept.).
Kurio, K.—An Intelligent Hybrid Method to Automatically Detect and Eliminate Experimental Measurement Errors for Linear Elastic Deformation Fields, 170-179 (June).
Kutt, L. M.—Measurement of Residual Stress Using Interferometric Moiracutee: A New Insight, 271-280 (Sept.).
Lai, H.-Y.—A New Method for Circular Grid Analysis in the Sheet Metal Forming Test, 190-196 (June).
Lambros, J.—A Combination Optical Method of Lateral Shearing Interferometry and Caustics, 376 (Dec.).
Lamparter, B.—A Radial Compression Test for Plastic Flow Studies, 7 (Mar.).
La Porta, F. A.—High-magnification Moiré Interferometer for Crack Tip Analysis of Steels, 90-95 (Mar.).
Laura, P.A.A.—Comments on "Interpretation of Experimental Data for Poisson's Ratio of Highly Nonlinear Materials," 430 (Dec.).
Lee, J.—A New Method for Circular Grid Analysis in the Sheet Metal Forming Test, 190-196 (June).
Li, M.—Initiation and Growth of Wrinkling Due to Nonuniform Tension in Sheet Metal Forming, 180-189 (June).
Li, N.—A Transversely Suspended Accelerometer, 160-163 (June).
Li, Z.—Damage Process Detection of a Ceramic Tile System by Acoustic Emission, 265-270 (Sept.).
Lim, B.-D.—Analysis of Deadweight Oscillation in a Deadweight Force Machine Using a Build-up System, 83-89 (Mar.).
Lin, S. T.—Blind-hole Residual Stress Determination Using Optical Interferometry, 60-67 (Mar.).
Liou, N. S.—A Moiré Microscope for Finite Deformation Micromechanical Studies, 351 (Dec.).
Liu, D.—Effects of Joining Techniques on Impact Perforation Resistance of Assembled Composite Plates, 46-53 (Mar.).
Liu, S.-C.—Residual Strain Measurement in Composites Using the Cure-referencing Method, 22-30 (Mar.).
Lu, F.—A Quartz-crystal-embedded Split Hopkinson Pressure Bar for Soft Materials, 1-6 (Mar.).
Lu, F.—A Technique for Dynamic Proportional Multiaxial Compression on Soft Materials, 226-230 (June).
Lu, H.—Deformation Measurements by Digital Image Correlation: Implementation of a Second-order Displacement Gradient, 393 (Dec.).
Luo, P. F.—Measurement of Curved-surface Deformation in Cylindrical Coordinates, 345 (Dec.).
Ma, Z.—Confined Compression: A Stable Homogeneous Deformation for Constitutive Characterization, 38-45 (Mar.).
Macdougall, D.—Determination of the Plastic Work Converted to Heat Using Radiometry, 298-306 (Sept.).
Maji, A. K.—Shape Measurement and Control of Deployable Membrane Structures, 154-159 (June).
Marcon, A. F.—Single-test Determination of the Friction Coefficient and Stress-strain Curve for Application in Metal-forming Analyses, 124-128 (June).
Martineau, R. L.—Expansion of Cylindrical Shells Subjected to Internal Explosive Detonations, 219-225 (June).
Meguid, S. A.—Photoelastic Analysis of the Singular Stress Field in a Bimaterial Wedge, 68-74 (Mar.).
Milke, J. G.—Notch Strengthening in Titanium Aluminides Under Monotonic Loading, 415 (Dec.).
Nagy, A.—An Experimental Method for Determining Dynamic Fracture Toughness, 401 (Dec.).
Nakabayashi, H.—An Intelligent Hybrid Method to Automatically Detect and Eliminate Experimental Measurement Errors for Linear Elastic Deformation Fields, 170-179 (June).
Nicolella, D. P.—Fracture Toughness of Fabrics as Composite Reinforcements, 408 (Dec.).
Nishioka, T.—An Intelligent Hybrid Method to Automatically Detect and Eliminate Experimental Measurement Errors for Linear Elastic Deformation Fields, 170-179 (June).
Niu, X.—Residual Strain Measurement in Composites Using the Cure-referencing Method, 22-30 (Mar.).
Nobre, J. P.—Use of the Hole-drilling Method for Measuring Residual Stresses in Highly Stressed Shot-peened Surfaces, 289-297 (Sept.).
Paloto, J. C.—Comments on "Interpretation of Experimental Data for Poisson's Ratio of Highly Nonlinear Materials," 430 (Dec.).
Papazian, J. M.—Measurement of Residual Stress Using Interferometric Moiré: A New Insight, 271-281 (Sept.).
Patanella, A.—Dynamic Compression-shear Response of Brittle Materials with Specimen Recovery, 321-330 (Sept.).
Patanella, A.—A Novel Dynamic Friction Experiment Using a Modified Kolsky Bar Apparatus, 138-153 (June).
Pierron, F.—Response to the Discussion of the Paper "Novel Procedure for Complete In-plane Composite Characterization Using a Single T-shaped Specimen," 97 (Mar.).
Piranda, J.—Identification of Stiffness Properties of Composite Tubes from Dynamic Tests, 211-218 (June).
Popelar, C. H.—An Experimental Method for Determining Dynamic Fracture Toughness, 401 (Dec.).
Prabhakaran, R—Discussion of "Novel Procedure for Complete Inplane Composite Characterization Using a Single T-shaped Specimen," 96-97 (Mar.).
Prabhu, S.—A Combination Optical Method of Lateral Shearing Interferometry and Caustics, 376 (Dec.).
Prakash, V.—A Moiré Microscope for Finite Deformation Micromechanical Studies, 351 (Dec.).
Qi, M.—Damage Process Detection of a Ceramic Tile System by Acoustic Emission, 265-270 (Sept.).
Rabin, Y.—Infrared Temperature Sensing of Mechanically Loaded Specimens: Thermal Analysis, 197-202 (June).
Raju, B. B.—Effects of Joining Techniques on Impact Perforation Resistance of Assembled Composite Plates, 46-53 (Mar.).
Ravi-Chandar, K.—Confined Compression: A Stable Homogeneous Deformation for Constitutive Characterization, 38-45 (Mar.).
Ravichandran, G.—Partition of Plastic Work into Heat and Stored Energy in Metals, 113-123 (June).
Ricci, S.—Best Achievable Modal Eigenvectors in Structural Damage Detection, 425 (Dec.).
Rittel, D.—Infrared Temperature Sensing of Mechanically Loaded Specimens: Thermal Analysis, 197-202 (June).
Robinson, J. S.—Residual Stress Prediction and Determination in 7010 Aluminum Alloy Forgings, 75-82 (Mar.).
Roman, I.—Experimental Evidence of Macroscopic Plastic Flow Nonhomogeneity Development in Uniaxial Tensile Test Samples, 261-264 (Sept.).
Rosakis, A. J.—Partition of Plastic Work into Heat and Stored Energy in Metals, 113-123 (June).
Rosakis, P.—Partition of Plastic Work into Heat and Stored Energy in Metals, 113-123 (June).
Rossit, C. A.—Comments on "Interpretation of Experimental Data for Poisson's Ratio of Highly Nonlinear Materials," 430 (Dec.).
Šali, S.—Measuring the Quality of Guitar Tone, 242-246 (Sept.).
Satapathy, S.—Deep Punching PMMA, 31-37 (Mar.).
Schmitt, D. R.—Inversion of Speckle Interferometer Fringes for Hole-drilling Residual Stress Determinations, 129-137 (June).
Scholtes, B.—Use of the Hole-drilling Method for Measuring Residual Stresses in Highly Stressed Shot-peened Surfaces, 289-297 (Sept.).
Schrems, K. K.—Theoretical, Experimental and Computational Mechanics of Fracture in Constrained Interlayers, 307-311 (Sept.).
Schwarz, R. C.—Measurement of Residual Stress Using Interferometric Moiré: A New Insight, 271-281 (Sept.).
Sciammarella, C. A.—Measurement of Bending Stresses in Shells of Arbitrary Shape Using the Reflection Moiré Method, 282-288 (Sept.).
Sciammarella, C. A.—Stress Analysis of Weldments by Holographic Moiré and the Finite Element Method, 15-21 (Mar.).
Sciammarella, F. M.—Measurement of Bending Stresses in Shells of Arbitrary Shape Using the Reflection Moiré Method, 282-288 (Sept.).
Sciammarella, F. M.—Stress Analysis of Weldments by Holographic Moiré and the Finite Element Method, 15-21 (Mar.).

Shimada, K.—A Device to Regulate Rotational Speed Using a Rotating Regulator with Electrorheological Fluid, 231-240 (June).
Singh, B.—Stress Analysis of Weldments by Holographic Moiré and the Finite Element Method, 15-21 (Mar.).
Smith, F. W.—Expansion of Cylindrical Shells Subjected to Internal Explosive Detonations, 219-225 (June).
Spigel, B. S.—Fracture Toughness of Fabrics as Composite Reinforcements, 408 (Dec.).
Starnes, M. A.—Shape Measurement and Control of Deployable Membrane Structures, 154-159 (June).
Surrel, Y.—Response to the Discussion of the Paper "Novel Procedure for Complete In-plane Composite Characterization Using a Single T-shaped Specimen," 97 (Mar.).
Szyszkowski, W.—On the Holographic Interferometry Fringe Gradient Method for Complete Surface Deformation Measurements, 164-169 (June).
Takashi, M.—Experimental Analysis of Rolling Contact Stresses in a Viscoelastic Strip, 203-210 (June).
Talbert, S.—A Radial Compression Test for Plastic Flow Studies, 7-9 (Mar.).
Tan, M. A.—Photoelastic Analysis of the Singular Stress Field in a Bimaterial Wedge, 68-74 (Mar.).
Tanner, D. A.—Residual Stress Prediction and Determination in 7010 Aluminum Alloy Forgings, 75-82 (Mar.).
Tavoularis, S.—A Radial Compression Test for Plastic Flow Studies, 7-9 (Mar.).
Tiziani, H. J.—Nondestructive Testing Using Temporal Phase Evaluation in Speckle Interferometry, 106-111 (Mar.).
Trentadue, B.—Measurement of Bending Stresses in Shells of Arbitrary Shape Using the Reflection Moiré Method, 282-288 (Sept.).
Trentadue, B.—Stress Analysis of Weldments by Holographic Moiré and the Finite Element Method, 15-21 (Mar.).
Tyas, A.—Experimental Evidence of Pochammer-Chree Strain Variations in Elastic Cylinders, 331-337 (Sept.).
Wang, C.-C.—A New Method for Circular Grid Analysis in the Sheet Metal Forming Test, 190-196 (June).
Watson, A. J.—Experimental Evidence of Pochammer-Chree Strain Variations in Elastic Cylinders, 331-337 (Sept.).
Weiss, B.—Noncontacting Strain Measurements at High Temperatures by the Digital Laser Speckle Technique, 98-105 (Mar.).
Weiss, H.—Noncontacting Strain Measurements at High Temperatures by the Digital Laser Speckle Technique, 98-105 (Mar.).
Welsh, J. S.—Development of an Electromechanical Triaxial Test Facility for Composite Materials, 312-320 (Sept.).
Xu, Y.—Dynamic Compression-shear Response of Brittle Materials with Specimen Recovery, 321-330 (Sept.).
Yam, L. H.—Three-dimensional Mode Shapes of a Tire Using Experimental Modal Analysis, 369 (Dec.).
Yao, W.—Damage Process Detection of a Ceramic Tile System by Acoustic Emission, 265-270 (Sept.).
Yoneyama, S.—Experimental Analysis of Rolling Contact Stresses in a Viscoelastic Strip, 203-210 (June).
Zagar, B. G.—Noncontacting Strain Measurements at High Temperatures by the Digital Laser Speckle Technique, 98-105 (Mar.).
Zeides, F.—Experimental Evidence of Macroscopic Plastic Flow Nonhomogeneity Development in Uniaxial Tensile Test Samples, 261-264 (Sept.).
Zhang, A. Q.—Three-dimensional Mode Shapes of a Tire Using Experimental Modal Analysis, 369 (Dec.).
Zhou, B.—A Quartz-crystal-embedded Split Hopkinson Pressure Bar for Soft Materials, 1-6 (Mar.).
Zuccarello, B.—Limitation of Fourier Transform Photoelasticity: Influence of Isoclinics, 384 (Dec.).